



TABEAU DE CONFIGURATION

		C80		Z90	Z70	F80			C50			C50+				
Dimension	Image	Largeur (L)		Hauteur max (H)	Sm m ²	L		H	S m	L		H	Sm			
		min	max			min	max			min	max					
Treuil		50	400	400	9	50	350	400	9	50	250	250	50	300	400	9
Moteur		60	400	400	15	60	350	400	9	50	250	250	50	300	400	9
Treuil		Maximum 4 brise-soleil				Máximo 4 brise-soleil				Maximum 5 brise-soleil 20Nm			Maximum 5 brise-soleil			25
Moteur		Maximum 5 brise-soleil 20Nm			36	Maximum 5 brise-soleil 20Nm				Maximum 5 brise-soleil 20Nm			Maximum 5 brise-soleil			25
Lame		80		90	70	80				50			50			
Epaisseur		0.42		0.42	0.42	0.42				0.24			0.24			
Treuil		+	+	+	+	+				+			+			
Moteur		+	+	+	+	+				+			+			
Corde (monocomande)										+						
Guidage C		+	+	+	+	+				+						
Cable		+	+	+	+	+				+						
Circulaire		+	+	+	+	+				+						
Autoportante		+	+	+	+	+				+						
Coloris		13 coloris		13 coloris	4 coloris	2 coloris				14 coloris			12 coloris			
Rail		56x58		56x58	56x58	56x58				40x40			56x58			
Barre de charge		T80		T90	T70	T80				T50			T50			